

## **DIVA - Digital Signage Player**

## The all-in-one player.

## Create and publish in minutes.

Built-in web-based interface, templates and tools to use for an easy content creation for any horizontal or vertical screen.





spinetix.com

## Tech Specs



Connectors & Ports	Video Audio Network Power supply	HDMI Line level, stereo Ethemet 1GbE, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3az Input: 100-240V, 50-60Hz/Output: 5V DC 3.6A max.
Size & Weight	Size Weight	Width: 5.9"/150mm, height: 0.9"/23mm, depth: 3.4"/86.5mm 12.3oz/350g
Player Engine	Layer composition	Background + non-overlapping zones
	Animation	Built-in playouts, apps
	Text	Unicode support (international text), bidirectional (right-to-left, left-to-right)
	Fonts	Built-in fonts (Western, Cyrillic, Arabic, Greek, Hebrew, Chinese, Japanese, Korean, Thai, Hindi, etc.)
Formats	Images	JPEG, PNG
	Media file formats	MPG, MP4, M4A, MOV, WMV
	Video codecs	Multi-video decoding capable, 1080p max, H.264/MPEG-4 AVC: HP@L4, MPEG-2: MP@HL, MPEG-4: ASP, WM9/VC-1: AP@L3
	Audio codecs	AAC-LC, HE-AAC, MPEG Layer I, II, III (MP3), WMAv2, AC3
	Data feeds	Built-in RSS app
Display	Aspect ratio	16:9 (horizontal, vertical)
. ,	Resolution	1080p (1920x1080), 720p (1280x720) at 50/60 Hz
Network	Protocols	DHCP, static IP, Zeroconf, IPv4, IPv6, Bonjour, HTTP
	Remote configuration	Built-in HTTP server, RPC
	Content transfer	Web browser upload
Storage	Internal	8GB solid state
Characteristics	Processor	DaVinci DM8148
	Memory	RAM: 1 GB, Bandwidth: 4.3GB/s
	Power consumption	8W
	Operating temperature	Ambient range 32 - 104°F/0 - 40°C, Relative humidity 10-90% noncondensing
	Storage temperature	-4- 122⁰F/-20 - 50°C
	Real-time clock (RTC)	Accuracy $\pm 1$ min./month, backup by supercap (40 days)
Tools		Built-in web-based content creation and scheduling tools
Warranty		3 Year Limited Hardware Warranty

Copyright ©2018 SpinetiX. All rigths reserved. The information contained in this document is non-contractual and is subject to change without notice.